



Primary Lithium Battery

CR14250SE

3.0V [Li-MnO₂]

1/2AA-size bobbin cell



BENEFITS

- High and Stable Operating Voltage
- Energy Density up to 830Wh/L
- Wide Operating Temperature Range (-40℃~+85℃)
- Low Self-discharge Rate (less than 1% per year after 1 year of storage at +25℃)

KEY FEATURES

- Optimized Battery Structure, Full Discharge Capacity
- Long Endurance
- No Passivation
- GB 8897.4-2008, IEC 60086.4:2014 and RoHS

MAIN APPLICATIONS

- Security System
- Smart Metering
- RFID and Tracking System
- Wireless Transmitting
- Smart Home Devices
- Military Devices

References Data

Electrical characteristics

Open circuit voltage (at 25℃) ≥3.10V

Nominal capacity 900mAh
(At +25℃, battery discharged at continuous current 0.5mA until voltage reaches cut-off voltage 2.0V. The capacity can vary at different temperature, discharge current or cut-off voltage.)

Maximum continuous current 7mA
(At +25℃, 2.0V cut-off, battery discharged for minimum 50% of rated capacity.)

Maximum pulse discharge current 70mA
(At +25℃, 2.0V cut-off, battery discharged for minimum 50% of rated capacity with max pulse for 3 seconds after 27 seconds break. The discharged capacity may vary according to the pulse characteristics, the temperature, and the cell's previous history. Fitting the cell with a capacitor may be recommended in severe conditions, consult HCB.)

Storage (recommended) ≤+30℃
(For more severe conditions, consult HCB) ≤75%RH

Operating temperature range -40℃~+85℃
(Operation above ambient temperature may lead to reduced capacity and lower voltage readings at the beginning of pulses, consult HCB.)

Primary Lithium Battery CR14250SE

3.0V [Li-MnO₂]

1/2AA-size bobbin cell




HCB
昊诚锂电

Physical characteristics

Diameter	14.0±0.5mm
Height	25.0±0.5mm
Typical weight	11.0g
Li metal content	0.32g

MSDS as per request
Diode (1N4007, 1N5819)
PTC (SRS175...)

Tag, wire, connector, etc. available




Dimensions in mm (GB1804-m)

WARNING:


- Do Not Short Circuit
- Do Not Recharge
- Do Not Puncture
- Do Not Crush
- Do Not Dismantle
- Do Not Incinerate
- Do Not Mix New and Used Batteries
- Do Not Heat Above 100°C

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact HCB for the latest information


1. Typical discharge profiles at 25°C
(at mid-discharge)



2. Voltage plateau versus Current and Temperature
(at discharge stable phase)



3. Storage characteristics



HCB BATTERY CO., LTD

Add: 37 Tianyuan Street, Dongxihu District, Wuhan, Hubei, China

P.O.: 430040

Tel: +86(0)27 83248452

Fax: +86(0)27 83248455

Email: haocheng@cnhcb.com

Web: www.cnhcb.com

No.: HCB-MKT.PM-S[V2.0 2023 05]