

# Primary Lithium Battery

## ER26500

3.6V Lithium-thionyl chloride[Li-SOCl<sub>2</sub>]  
C-size bobbin cell



### Benefits

- High and Stable Voltage
- Energy Density up to 590Wh/kg
- Long Shelf Life (less than 1% per year after 1 year of storage at +25°C)
- Wide Operating Temperature (-55°C~+85°C)

### Key Features

- Stainless Steel Container
- Glass to Metal Hermetic Sealing
- Non-flammable Electrolyte
- CE, UL(MH10060) and UN38.3 Certified

### Main Applications

- Security System
- Smart Metering
- RFID / IoT System
- Wireless Transmitting
- Smart Home Devices
- Military Devices

*New cell\*:*

*Refer to the cells that are stored within two months at no higher than +25°C.*

### Electrical Characteristics

**Open circuit voltage (at 25°C)** **≥3.65V**

**Nominal capacity** **8500mAh**

(At +25°C, battery discharged at continuous current 3mA until voltage reaches cut-off voltage 2.0V. The capacity can vary at different temperature, discharge current or cut-off voltage.)

**Maximum continuous current** **150mA**

(New cell\*, at +25°C, 2.0V cut-off, battery discharged for minimum 50% of nominal capacity.)

**Maximum pulse discharge current** **300mA**

(300 mA/0.1 second pulses, drained every 2 minutes at +25°C from undischarged the new cell with 10 uA base current, yield voltage reading above 3.0V. The readings may vary according to the pulse characteristics, the temperature, and the's previous history. Fitting the cell with a capacitor may be recommended in severe conditions, consult HCB.)

**Storage (recommended)** **≤30°C**  
(For more severe conditions, consult HCB.) **≤75%RH**

**Operating temperature range** **-55°C~+85°C**

(Operation above ambient temperature may lead to reduced capacity and lower voltage readings at the beginning of pulses, consult HCB.)

### HCB BATTERY CO., LTD

Add: Special No 1. Taizhong Avenue, Gaoqiao Industrial Park, Wujiashan Economic Development Zone, Wuhan, P.R.China

P.O.: 430040  
Tel: +86(0)27 83248452  
Fax: +86(0)27 83248455

Email: haocheng@cnhcb.com  
Web: www.cnhcb.com  
No.: HCB-MKT.PM-S[V1.0 2017 02]

# Primary Lithium Battery ER26500


3.6V Lithium-thionyl chloride[Li-SOCl<sub>2</sub>]  
C-size bobbin cell

## Physical Characteristics

<b>Diameter</b>	<b>25.6±0.2mm</b>
<b>Height</b>	<b>49.1±0.5mm</b>
<b>Typical weight</b>	<b>53.0g</b>
<b>Lithium metal content</b>	<b>2.4g</b>

MSDS as per request  
Diode (1N4007, 1N5819)  
PTC (SRS175...)

Tag, wire, connector, etc. available




Dimensions in mm


## WARNING:

- Do not short circuit
- Do not recharge
- Do not puncture
- Do not crush
- Do not dismantle
- Do not incinerate
- Do not mix new and used batteries
- Do not heat above 100°C

1. Typical discharge profiles at 25°C  
(at the mid-discharge)



2. Voltage plateau versus Current and Temperature  
(at the mid-discharge)



3. Storage characteristics

